



BLACK PATINATING WAX



250ml

Liberon Black Patinating Wax is used for adding a coloured finish, highlighting areas or creating striking effects on all types of interior materials. It is ideal for ageing modern furniture, disguising repairs to old and new furniture, and highlighting areas on finished pieces and decorative carvings. It is suitable for use on wood, metal, gilt, plaster, stone, MDF and papier-mâché.

- **Special effect wax used for adding a coloured finish, highlighting areas or creating striking effects**
- **Suitable for use on wood, metal, gilt, plaster, stone, MDF and papier-mâché**

PREPARATION

Ensure the surface is clean, dry and free from any previous finishing materials.

APPLICATION

Wipe onto the surface with a cloth or brush and allow to dry for two to three minutes before removing as much or as little of the excess as you wish with a clean lint-free cloth or Liberon Ultrafine Steel Wool (Grade 0000). To use the wax as a coloured finish on bare wood, work a thin coat into the wood with Liberon Ultrafine Steel Wool (Grade 0000), allow to become touch dry and buff.

To remove large areas of Special Effect Wax, use Liberon Black Bison Paste Wax Neutral and buff. For a water-resistant finish, use Liberon Finishing Oil applied with a lint-free cloth or Liberon Ultrafine Steel Wool (Grade 0000).

Important: Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

CAUTION: Risk of self-combustion. Wet with water any textiles or tools soiled with the product and dispose of them in a tightly closed container. Remove as much of the product as possible from the tools after use. Do not dispose of residues and washing water/solvents in the sink, toilet, sewer, bin, etc., in order to avoid discharge into the environment.

HINTS & TIPS

Try Liberon Special Effects Waxes in conjunction with the Liberon Gilt Cream for an even wider selection of effects.



Min. 5 mins



250ml = 8-12m²



Brush, Cloth or
Steel Wool



White Spirit

This product should be used in accordance with the manufacturer's instructions. Recommendations are for guidance only since conditions of use are completely beyond our control. For technical or practical information on this or other Liberon products please contact Liberon Technical Services on 01797 367555.

This notice is intended to provide information. The information is based on our current knowledge and experience based on conditions of use that comply with the standards or DTU in force. Given the multiplicity of factors that can influence the use of our products, they cannot exempt the user from his own experiences. No legal warranty can be derived from our information. This data sheet supersedes all previous editions.