LIBÉRON

LIMING WAX



250ml 500ml

Liberon Liming Wax is a white wax used to create a limed effect on oak and other interior hardwoods.

Special effects wax
Easy to use

PREPARATION

Ensure the surface is clean, dry and free from any previous finishes. Open the grain with a Liberon Liming Brush. On softwoods such as pine, use a wire brush or coarse abrasive paper to score the timber. If you wish to enhance the effect, colour the wood with Liberon Palette Wood Dye before applying the liming wax. Liberon Palette Wood Dyes are available in a wide selection of wood shades.

APPLICATION

Work the liming wax into the grain of the wood with Liberon Ultrafine Steel Wool (0000) or a lint-free cotton cloth and wipe over with a clean cloth to remove excess. Allow to dry for 3 minutes. Remove the white haze using a cloth and Liberon Black Bison Paste Wax Neutral, or if a water-resistant finish is 500ml the EU required, with Liberon Finishing Oil. Apply a second coat of Wax Polish Black Bison and buff or add another coat of oil. The more coats of oil that are applied, the greater the water resistance and the higher the shine.

Important: Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

CAUTION: Risk of self-combustion. Wet with water any textiles or tools soiled with the product and dispose of them in a tightly closed container. Remove as much of the product as possible from the tools after use. Do not dispose of residues and washing water/solvents in the sink, toilet, sewer, bin, etc., in order to avoid discharge into the environment.



This product should be used in accordance with the manufacturer's instructions. Recommendations are for guidance only since conditions of use are completely beyond our control. For technical or practical information on this or other Liberon products please contact Liberon Technical Services on 01797 367555.

This notice is intended to provide information. The information is based on our current knowledge and experience based on conditions of use that comply with the standards or DTU in force. Given the multiplicity of factors that can influence the use of our products, they cannot exempt the user from his own experiences. No legal warranty can be derived from our information. This data sheet supersedes all previous editions.

Liberon Limited, Mountfield Industrial Estate, New Romney, Kent TN28 8XU, Tel: +44 (0) 1797 367555, Email: liberon.uksales@v33.com, www.liberon.co.uk Head Office - V33 Group, Rue de la Croix Bernard BP 1, F-39210 DOMBLANS cedex, Tel: +33 3 84 35 00 33, www.groupev33.com